



Nr. / No.	Länge / Length (m)
93922	0.60
93918	1.00
93181	1.80
93920	3.00
93921	5.00

**Micro-USB Daten- und Ladekabel**

- Verbinder: USB-A Stecker > Micro USB-B St.
- Innenleiter: AWG28 (4 x 7/0.12mm) Kupfer
- Isolierung: PVC; schwarz
- Schirmung: doppelt; 1mm AL-Folie + (44/0.12mm) Geflecht
- USB Standard: High Speed USB 2.0
- Datenrate: max. 480Mbit/s
- RoHS-konform

**Micro USB data and charging cable**

- USB-A plug > Micro USB-B plug
- Inner conductor: AWG28 (4 x 7/0.12mm) copper
- Insulation: PVC; black
- Shielding: double; 1mm AL foil + (44/0.12) Braiding
- USB Standard: High Speed USB 2.0
- Data rate: max. 480Mbps
- RoHS compliant

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 30.07.2014	tf	USB MICRO-B SCHWARZ	
		gepr.: 30.07.2014	tf		
		Norm:		Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change				V1	

